

DATASHEET

MARK 1 PLUS



GENERAL

Art.Nr:	A-031	Standards:	EN 12841:2006/C, EN 341:2011/2A
GTIN:	4030281180289	Net weight:	0.47 kg
E-class number:	40-21-01-01	Gross weight:	0.47 kg
Customs tariff number:	76169990		

DATASHEET

MARK 1 PLUS

The abseil device Mark 1 Plus is the only repelling device meeting EN 341-2A:2011 and EN 12841-C:2006. Usage according to EN 341-2A: In combination with the Skylotec Super Static 11 mm-rope, Mark 1 Plus can be used with weights 30 - 160kg and a max. abseil height of 190m. Usage according to EN 12841-C: In combination with ropes meeting EN 1891-A , Mark 1 Plus can be used with ropes between 9 - 12mm. Max. weight load: 9mm = 130kg 10-12mm = 200kg with panic feature

FEATURES

Colour:	Black
Lifting function:	No
Maximum load 1 person:	141.00 kg
Maximum load 2 persons:	200.00 kg
Maximum lifetime:	30 years
Maximum number of persons:	2
Maximum load:	200.00 kg
Minimum compatible rope diameter:	9.00 mm
Maximum compatible rope diameter:	12.00 mm
Max. Abseil speed:	2.00 m/s
Minimum temperature:	-35 °C
Maximum temperature:	60 °C
Panic function:	Yes
Rescue function:	No

MATERIAL

Material:	Aluminium, Polyamide
-----------	----------------------