

DATASHEET

TUNER PRO TWIN



GENERAL

Art.Nr:	L-1018
GTIN:	8053841303047
E-class number:	40-21-08-13
Customs tariff number:	56090000

Standards:	EN 358:2018
Net weight:	0.34 kg
Gross weight:	0.42 kg

DATASHEET

TUNER PRO TWIN

The multi-purpose Y-shaped holding rope was specially developed for working on ropes, at height and for rescue operations and is certified in accordance with EN 358. Despite its compact dimensions and low weight, it offers one of the highest working loads on the market.

The double regulator has a patented, movable system that ensures immediate and safe blocking of the rope - regardless of the shape of the connecting element used in accordance with EN 362. The special geometry of the regulator allows precise and smooth adjustment of the rope length, with intuitive release using just one hand: simply hold the regulator and press the release button, even with a light load.

The lanyard complies with the EN 1891-A standard, has a diameter of 9.6 mm, is lightweight, flexible and designed for the most intensive use. A sewn-on eyelet enables attachment to the harness using a carabiner or connecting element in accordance with EN 362. Elastic end loops ensure that the free rope ends can be positioned securely during use. The maximum length of the individual rope sections is 1.3 meters.

MORE INFORMATION

TUNER PRO – Versatile lanyard for workplace positioning, restraint systems and rescue at height
<https://www.skylotec.com/eu_en/tunerpro>

FEATURES

Colour: Black, Orange

Maximum lifetime: 12 years

Minimum temperature: -30 °C

Maximum temperature: 50 °C

Patent status: Patent pending

Individually tested: No

100% quality control: Yes

DIMENSIONS

length_lanyard: 1.30 m

Lanyard rope diameter: 9.60 mm

MATERIAL

Material: Aluminium, Polyamide